



Metaspace

 $8\ 215\ 356\ 059$ 6 × 6,3 W, 3647 lm, 3000 K warm white, lateral wide beam 46° / 142°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminarie for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient metallized PC reflector, integral driver (AC/DC), CRI > 80, 3, service life L80/B20 > 50.000 h,

Beam angle (FWHM): 46° / 142°, luminous flux: 3647 lm, wattage: 38 W, delivered lumens 97 lm/W, protection type IP65, protection class I, impact resistance IKo8, windage area 0,056 m², dimensions: \varnothing 376 mm, width 112 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Input voltage DC

Wattage 38 W

Delivered lumens 97 lm/W

Light source LED 3000 K

Color Rendering Index CRI > 80

Colour tolerance 3

Lifetime ta 25° C L80/B20 > 50.000 h

Control gear on / off

Input voltage AC 220 - 240 V

Voltage protection 6 kV L/N | 10 kV L/PE

220 - 240 V

Luminaires per B16A / C16A 20 / 33

Beam angle (FWHM) 46° / 142°
Housing colour silver grey
Protection type IP65
Protection class I
Impact resistance IK08
Windage area 0,056m²

Dimensions Ø 376 mm, width 112 mm

Weight 5,10 kg Max. ambient temperature ta 40 $^{\circ}$