


Metaspace

8 217 357 389

 $6\times6,3$ W, 3522 lm, 2700 K warm white, Zhaga 18 - up,

asymmetrical wide beam 64° / 133°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminarie for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient metallized PC reflector, integral driver (AC/DC), CRI > 80, 3, service life 180/B20 > 50.000 h,

Beam angle (FWHM): 64° / 133°, luminous flux: 3522 lm, wattage: 38 W, delivered lumens 93 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,056 m², dimensions: Ø 396 mm, width 112 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage 38 W

Delivered lumens 93 lm/W

Light source LED 2700 K

Color Rendering Index CRI > 80

Colour tolerance 3

Voltage protection $6 \text{ kV L/N} \mid 10 \text{ kV L/PE}$

Luminaires per B16A / C16A 20 / 33

Beam angle (FWHM) 64° / 133°
Housing colour silver grey
Protection type IP65

Protection class II
Impact resistance IK08

Windage area 0,056m²

Dimensions Ø 396 mm, width 112 mm
Weight 5,10 kg

Max. ambient temperature ta 40°