





Metaspot 2 Darkring Optic

8 232 046 159

3 × 13 W, 2782 lm, 3000 K warm white, DALI, wide beam 48°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, mounting bracket: 2 drilled holes \varnothing 9 mm, spacing 40 mm, 1 centre hole \varnothing 14 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, light source completely shielded, high gloss aluminium reflector, integral, dimmable driver (DALI), CRI > 80, 3, service life L80/B10 > 50.000 h, Beam angle (FWHM): 48°, luminous flux: 2782 lm, wattage: 39 W, delivered lumens 72 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,042 m², dimensions: \varnothing 176 mm, width 244 mm, weight 3.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	39 W	Beam angle (FWHM)	48°
Delivered lumens	72 lm/W	Housing colour	black RAL 7021
Light source	LED 3000 K	Power supply cable	\varnothing 6 – 11 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	3	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,042m ²
Input voltage AC	220 – 240 V	Dimensions	\varnothing 176 mm, width 244 mm
Input voltage DC	220 – 240 V	Weight	3,80 kg
Voltage protection	6 kV L/N 10 kV L/PE	Max. ambient temperature ta	50°
Luminaires per B16A / C16A	20 / 33		