





Metaspot 2 Darkring Optic

8 232 057 049

3 × 13 W, 2666 lm, 2700 K warm white, medium wide beam 27°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, mounting bracket: 2 drilled holes Ø 9 mm, spacing 40 mm, 1 centre hole Ø 14 mm, tilt range: 180°, cable gland: M20, connecting terminal: 3 pole, light source completely shielded, high gloss aluminium reflector, integral driver (AC/DC), CRI > 80, 3, service life L80/B10 > 50.000 h, Beam angle (FWHM): 27°, luminous flux: 2666 lm, wattage: 39 W, delivered lumens 68 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,042 m², dimensions: Ø 176 mm, width 244 mm, weight 3.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	39 W	Beam angle (FWHM)	27°
Delivered lumens	68 lm/W	Housing colour	silver grey
Light source	LED 2700 K	Power supply cable	Ø 6 – 11 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	3	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	on / off	Windage area	0,042m ²
Input voltage AC	220 – 240 V	Dimensions	Ø 176 mm, width 244 mm
Input voltage DC	220 – 240 V	Weight	3,80 kg
Voltage protection	6 kV L/N 10 kV L/PE	Max. ambient temperature ta	50°
Luminaires per B16A / C16A	20 / 33		