




Metaspot 3

8 243 049 019

49 W, 1442 lm, RGBW (3000 K) warm white, DMX, narrow beam 9°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, mounting bracket: 2 drilled holes \varnothing 9 mm, spacing 40 mm, 1 centre hole \varnothing 14 mm, tilt range: 180°, cable gland: M20, connecting terminal: 6 pole, light source completely shielded, high gloss aluminium reflector, integral driver (AC/DC), Beam angle (FWHM): 9°, luminous flux: 1442 lm, wattage: 49 W, delivered lumens 29 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m², dimensions: \varnothing 201 mm, width 272 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

| | | | |
|----------------------------|-------------------|-----------------------------|------------------------------------|
| Wattage | 49 W | Beam angle (FWHM) | 9° |
| Delivered lumens | 29 lm/W | Housing colour | black RAL 7021 |
| Light source | LED RGBW (3000 K) | Protection type | IP65 |
| Control gear | DMX | Protection class | I |
| Input voltage AC | 120 – 277 V | Impact resistance | IK08 |
| Input voltage DC | 120 – 250 V | Windage area | 0,055m ² |
| Luminaires per B16A / C16A | 22 / 22 | Dimensions | \varnothing 201 mm, width 272 mm |
| | | Weight | 5,00 kg |
| | | Max. ambient temperature ta | 35° |