




Metaspot 3

8 243 059 059

49 W, 1937 lm, RGBW (3000 K) warm white, DMX, wide beam 57°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, mounting bracket: 2 drilled holes \varnothing 9 mm, spacing 40 mm, 1 centre hole \varnothing 14 mm, tilt range: 180°, cable gland: M20, connecting terminal: 6 pole, light source completely shielded, high gloss aluminium reflector, integral driver (AC/DC), Beam angle (FWHM): 57°, luminous flux: 1937 lm, wattage: 49 W, delivered lumens 40 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m², dimensions: \varnothing 201 mm, width 272 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	49 W	Beam angle (FWHM)	57°
Delivered lumens	40 lm/W	Housing colour	silver grey
Light source	LED RGBW (3000 K)	Protection type	IP65
Control gear	DMX	Protection class	I
Input voltage AC	120 – 277 V	Impact resistance	IK08
Input voltage DC	120 – 250 V	Windage area	0,055m ²
Luminaires per B16A / C16A	22 / 22	Dimensions	\varnothing 201 mm, width 272 mm
		Weight	5,00 kg
		Max. ambient temperature ta	35°