




## Metaspot 3

8 243 267 179

67 W, 4197 lm, 2700 K warm white, DALI,  
linear, rotatable 9° / 36°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, tool-free twist closure, for installation on poles  $\varnothing$  60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes  $\varnothing$  9 mm, spacing 95 mm, 1 centre hole  $\varnothing$  40 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, light source completely shielded, high gloss aluminium reflector, integral, dimmable driver (DALI), CRI > 80, 3, service life L80/B10 > 50.000 h, Beam angle (FWHM): 9° / 36°, luminous flux: 4197 lm, wattage: 67 W, delivered lumens 63 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m<sup>2</sup>, dimensions:  $\varnothing$  201 mm, width 272 mm, weight 5.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

## Specification

Wattage	67 W	Beam angle (FWHM)	9° / 36°
Delivered lumens	63 lm/W	Housing colour	white RAL 9002
Light source	LED 2700 K	Power supply cable	$\varnothing$ 6 - 11 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	3	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,055m <sup>2</sup>
Input voltage AC	220 - 240 V	Dimensions	$\varnothing$ 201 mm, width 272 mm
Input voltage DC	220 - 240 V	Weight	5,40 kg
Voltage protection	2 kV L/N   4 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	10 / 16		