



## Metaspot 1

 $8\ 245\ 256\ 129$   $_{15}$  W, 1171 lm, 3000 K warm white, DALI, linear, vertical 36° / 9°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, for installation on poles Ø 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes Ø 9 mm, spacing 95 mm, 1 centre hole Ø 40 mm, tilt range: 90°, 360° adjustable, cable gland: M16, connecting terminal: 5 pole, light source completely shielded, high gloss aluminium reflector, inegral, dimmable driver (DALI), CRI > 80, 3, service life L80/B10 > 50.000 h,

Beam angle (FWHM): 36° / 9°, luminous flux: 1171 lm, wattage: 15 W, delivered lumens 78 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,026 m², dimensions: Ø 124 mm, width 180 mm, weight 2.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

## Specification

15 W Wattage Delivered lumens 78 lm/W Light source LED 3000 K Color Rendering Index CRI > 80 Colour tolerance Lifetime ta 25° C L80/B10 > 50.000 h Control gear DALI Input voltage AC 220 – 240 V Input voltage DC 220 - 240 V 2 kV L/N | 4 kV L/PE Voltage protection Luminaires per B16A / C16A 50 / 85

36°/9° Beam angle (FWHM) Housing colour silver grey Power supply cable Ø 6 – 11 mm IP65 Protection type Protection class Impact resistance **IK08** 0,026m² Windage area Dimensions Ø 124 mm, width 180 mm Weight 2,10 kg 40° Max. ambient temperature ta