





Metaspot 3 Darkring Optic

8 233 056 159

3 × 19 W, 4288 lm, 3000 K warm white, DALI, wide beam 54°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, mounting bracket: 2 drilled holes \varnothing 9 mm, spacing 40 mm, 1 centre hole \varnothing 14 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, light source completely shielded, high gloss aluminium reflector, integral, dimmable driver (DALI), CRI > 80, 3, service life L80/B10 > 50.000 h, Beam angle (FWHM): 54°, luminous flux: 4288 lm, wattage: 58 W, delivered lumens 74 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m², dimensions: \varnothing 200 mm, width 272 mm, weight 4.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	58 W	Beam angle (FWHM)	54°
Delivered lumens	74 lm/W	Housing colour	silver grey
Light source	LED 3000 K	Power supply cable	\varnothing 6 – 11 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	3	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,055m ²
Input voltage AC	220 – 240 V	Dimensions	\varnothing 200 mm, width 272 mm
Input voltage DC	220 – 240 V	Weight	4,40 kg
Voltage protection	6 kV L/N 8 kV L/PE	Max. ambient temperature ta	45°
Luminaires per B16A / C16A	10 / 16		