




Metaspot 2

8 242 267 089

35 W, 3299 lm, 2700 K warm white, Street Optic 51 $^{\circ}$ / 141 $^{\circ}$







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, for installation on poles \varnothing 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes \varnothing 9 mm, spacing 95 mm, 1 centre hole \varnothing 40 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), CRI > 80, 3, service life L90/B10 > 50.000 h,

Beam angle (FWHM): 51° / 141°, luminous flux: 3299 lm, wattage: 35 W, delivered lumens 96 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,042 m², dimensions: Ø 176 mm, width 244 mm, weight 3.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage 35 W

Delivered lumens 96 lm/W

Light source LED 2700 K

Color Rendering Index CRI > 80

Colour tolerance 3

Lifetime ta 25° C L90/B10 > 50.000 h

Control gear on / off

51°/141° Beam angle (FWHM) Housing colour white RAL 9002 Power supply cable Ø 6 – 11 mm Protection type IP65 Protection class Impact resistance **IK08** Windage area 0,042m² Dimensions Ø 176 mm, width 244 mm Weight 3,70 kg

Weight 3.70 k Max. ambient temperature ta 45°