







Minispot 2 - 48 V

8 925 045 049 9 W, 576 lm, 4000 K neutral white, medium wide beam 23°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, silicon gasket, with 2 stainless steel screws, mounting bracket: 1 long hole \varnothing 7 mm, spacing 18 mm, 1 center hole \varnothing 8.5 mm, tilt range: 185°, cable gland: M20, connecting terminal: 3 pole, highly efficient faceted rotationally symmetrical reflector, Radial louvre, Constant current control (48 V DC), CRI > 80, 3, service life L90/B10 > 50.000 h, Beam angle (FWHM): 23°, luminous flux: 576 lm, wattage: 9 W, delivered lumens 64 lm/W, protection type IP65, protection class III, impact resistance IK08, windage area 0,01 m², dimensions: \varnothing 80 mm, width 121 mm, weight 0.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Input voltage DC

Wattage 9 W

Delivered lumens 64 lm/W

Light source LED 4000 K

Color Rendering Index CRI > 80

Colour tolerance 3

Lifetime ta 25° C L90/B10 > 50.000 h

Control gear on / off

48

Beam angle (FWHM) 23°
Housing colour blac

Housing colour black RAL 7021

Power supply cable Ø 6 – 11 mm

Protection type IP65
Protection class III
Impact resistance IK08
Windage area 0,01m²

Dimensions Ø 80 mm, width 121 mm

Weight o,80 kg
Max. ambient temperature ta 35°