




## Minispot 2 - 48 V

8 925 049 359

3 W, 155 lm, RGBW Casambi,  
wide beam 13°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, silicon gasket, with 2 stainless steel screws, mounting bracket: 1 long hole  $\varnothing$  7 mm, spacing 18 mm, 1 center hole  $\varnothing$  8.5 mm, tilt range: 185°, cable gland: M20, connecting terminal: 6 pole, Radial louvre, highly efficient optics made of transparent thermoplastic for precise lighting tasks, Constant current control (48 V DC), 80, service life L90/B > 50.000 h, Beam angle (FWHM): 13°, luminous flux: 155 lm, wattage: 3 W, protection type IP65, protection class III, impact resistance IK08, windage area 0,01 m<sup>2</sup>, dimensions (LxHxW): 66 x 125 x 116 mm, weight 0.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

## Specification

Wattage	3 W	Beam angle (FWHM)	13°
Light source	LED RGBW	Housing colour	black RAL 7021
Color Rendering Index	80	Protection type	IP65
Lifetime ta 25° C	L90/B > 50.000 h	Protection class	III
Control gear	Casambi	Impact resistance	IK08
		Windage area	0,01m <sup>2</sup>
		Dimensions	66 x 125 x 116 mm
		Weight	0,80 kg