








Minispot 2 - 48 V

 $8\,925\,057\,029$ $8\,W,\,484\,lm,\,2700\,K$ warm white, linear vertical $34^\circ/7^\circ$







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, silicon gasket, with 2 stainless steel screws, mounting bracket: 1 long hole \varnothing 7 mm, spacing 18 mm, 1 center hole \varnothing 8.5 mm, tilt range: 185°, cable gland: M20, connecting terminal: 3 pole, highly efficient faceted rotationally symmetrical reflector, Radial louvre, Constant current control (48 V DC), CRI > 80, 3, service life L90/B10 > 50.000 h,

Beam angle (FWHM): 34° / 7° , luminous flux: 484 lm, wattage: 8 W, delivered lumens 60 lm/W, protection type IP65, protection class III, impact resistance IK08, windage area 0.01 m², dimensions: \emptyset 80 mm, width 121 mm, weight 0.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage 8 W

Delivered lumens 60 lm/W

Light source LED 2700 K

Color Rendering Index CRI > 80

Colour tolerance 3

Lifetime ta 25° C L90/B10 > 50.000 h

Control gear on / off

Input voltage DC 48

34°/7° Beam angle (FWHM) Housing colour silver grey Power supply cable Ø 6 – 11 mm Protection type IP65 Protection class Ш Impact resistance **IK08** Windage area $0,01m^{2}$ Dimensions Ø 80 mm, width 121 mm

Weight 0,80 kg
Max. ambient temperature ta 35°