



## Monospace

8 252 046 189

5 × 10,8 W, 6643 lm, 3000 K warm white, DALI, asymmetrical wide beam 60° / 138°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, mounting bracket: 2 drilled holes Ø 7 mm, spacing 40 - 50 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, highly efficient metallized PC reflector, integral driver (DALI), CRI > 80, 3 SCDM, service life L80/B20 > 50.000 h, Beam angle (FWHM): 60° / 138°, luminous flux: 6643 lm, wattage: 54 W, delivered lumens 123 lm/W, protection type IP67, protection class II, impact resistance IK08, windage area 0,063 m², dimensions (L×H×W): 362 × 67 × 308 mm, weight 4.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



## Specification

|                       |                    |                             |                   |
|-----------------------|--------------------|-----------------------------|-------------------|
| Wattage               | 54 W               | Beam angle (FWHM)           | 60° / 138°        |
| Delivered lumens      | 123 lm/W           | Housing colour              | black RAL 7021    |
| Light source          | LED 3000 K         | Power supply cable          | Ø 5 - 14 mm       |
| Color Rendering Index | CRI > 80           | Protection type             | IP67              |
| Colour tolerance      | 3 SCDM             | Protection class            | II                |
| Lifetime ta 25° C     | L80/B20 > 50.000 h | Impact resistance           | IK08              |
| Control gear          | DALI               | Windage area                | 0,063m²           |
|                       |                    | Dimensions                  | 362 × 67 × 308 mm |
|                       |                    | Weight                      | 4,50 kg           |
|                       |                    | Max. ambient temperature ta | 35°               |