





Minispot 2 - 48 V

 $8\,925\,055\,029$ $8\,W$, 534 lm, 4000 K neutral white, linear vertical 34° $/\,7^\circ$







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, silicon gasket, with 2 stainless steel screws, mounting bracket: 1 long hole \varnothing 7 mm, spacing 18 mm, 1 center hole \varnothing 8.5 mm, tilt range: 185°, cable gland: M20, connecting terminal: 3 pole, highly efficient faceted rotationally symmetrical reflector, Constant current control (48 V DC), CRI > 80, max 3 SDCM, service life L90/B10 > 50.000 h,

Beam angle (FWHM): 34° / 7° , luminous flux: 534 lm, wattage: 8 W, delivered lumens 67 lm/W, protection type IP65, protection class III, impact resistance IKo8, windage area 0,01 m², dimensions: \emptyset 80 mm, width 121 mm, weight 0.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

8 W Wattage Delivered lumens $67 \, lm/W$ Light source LED 4000 K Color Rendering Index CRI > 80 max 3 SDCM Colour tolerance L90/B10 > 50.000 h Lifetime ta 25° C on / off Control gear Input voltage DC 48

Beam angle (FWHM) 34° / 7°
Housing colour silver grey

Power supply cable Ø 6 – 11 mm

Protection type IP65

Protection class III
Impact resistance IK08

Windage area 0,01m²

Dimensions Ø 80 mm, width 121 mm

Weight 0,80 kg
Max. ambient temperature ta 35°