



Nightspot A

8 965 246 049  
4 × 1,5 W, 439 lm, 3000 K warm white,  
medium wide beam 6°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, base can be rotated 360°, 1 drilled hole Ø 6.5 mm, tilt range: 110°, cable gland: with 2.5 m cable H05RN-F3G1 and safety plug, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), typ 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 6°, luminous flux: 439 lm, wattage: 8 W, delivered lumens 55 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,015 m², dimensions: Ø 66 mm, width 17 mm, weight 1.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

|                            |                      |                             |                      |
|----------------------------|----------------------|-----------------------------|----------------------|
| Wattage                    | 8 W                  | Beam angle (FWHM)           | 6°                   |
| Delivered lumens           | 55 lm/W              | Housing colour              | black RAL 7021       |
| Light source               | LED 3000 K           | Protection type             | IP65                 |
| Color Rendering Index      | typ 80               | Protection class            | I                    |
| Colour tolerance           | max 2 SDCM           | Impact resistance           | IK08                 |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Windage area                | 0,015m²              |
| Control gear               | on / off             | Dimensions                  | Ø 66 mm, width 17 mm |
| Input voltage AC           | 100 – 240 V          | Weight                      | 1,20 kg              |
| Input voltage DC           | 135 – 340 V          | Max. ambient temperature ta | 50°                  |
| Voltage protection         | 1 kV L/N   2 kV L/PE |                             |                      |
| Luminaires per B16A / C16A | 157 / 254            |                             |                      |