




Nightspot B Gobo Projector

8 987 244 619
0 W, 6500 K cold white, DALI,
150 mm focal length



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of extruded aluminum and corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, for installation on poles Ø 60-100mm, adjustable aluminum mounting base, powder coated: 2 drilled holes Ø 9mm, tilt range: 80°, cable gland: M20, connecting terminal: 5 pole, tilt range: 180°, focusable projection lens for precise light control and sharp-edged image projections, integral driver (dimmbare DALI), wattage: 0 W, protection type IP67, protection class II, impact resistance IK08, windage area 0,085 m², dimensions (L×H×W): 425 × 300 × 240 mm, weight 7.9 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP67 IK08

Specification

Wattage	0 W	Housing colour	black RAL 7021
Light source	LED 6500 K	Protection type	IP67
Control gear	DALI	Protection class	II
		Impact resistance	IK08
		Windage area	0,085m²
		Dimensions	425 × 300 × 240 mm
		Weight	7,90 kg